

# TECHNICAL DATA SHEET



Advanced Cleaning Chemistry™

## DuraGloss



Liberty  
Cleaning Supplies  
& Services

Distributed by:

TheFriendlyProfessional

[www.libertycleaning.ca](http://www.libertycleaning.ca)  
[info@libertycleaning.ca](mailto:info@libertycleaning.ca)

413 Colborne  
Brantford, Ontario  
N3S 3N5

### CLASSIFICATION:

- Modified acrylic floor finish

### PACKAGING:

Jug	Pail	Drum
4L	18.9L	210L

### DESCRIPTION:

- DuraGloss** Floor Finish provides a high level of scuff resistance in combination with excellent durability, *providing beneficial maintenance labour savings*; requiring less frequent burnishing in comparison to conventional finishes.
- DuraGloss** Floor Finish responds well to burnishing with 1500 rpm to 3000 rpm equipment using a light synthetic / natural hair blend pad.
- DuraGloss** Floor Finish is completely white in both liquid and dried forms, undergoing no yellowing / discolouration caused by age or uv light.

### CHEMICAL AND PHYSICAL PROPERTIES:

- Appearance White opaque liquid
- Odour Mild acrylic + ammonia
- pH 8 – 9
- Specific Gravity 1.02
- Viscosity Less than 20 cps
- Nonvolatiles / Solids 20%

### USE DIRECTIONS:

- Application:** Prepare floor by scrubbing with a Sanilabs neutral cleaner or Sanilabs Tuff-Scrub, or by stripping with a Sanilabs stripper according to label directions. Rinse well. Apply **DuraGloss** Floor Finish undiluted in uniform coats (35-75 m<sup>2</sup>/L; 1500-3000 ft<sup>2</sup>/ US gal) with a clean floor finish string mop or flat mop. Allow adequate dry time between coats (30 minutes minimum, or 15 minutes after dry to touch, whichever is longer). No sealer is typically required, except for very porous floors (e.g. terrazzo), or if additional stain resistance is needed.
- Maintenance:** Dust mop and clean daily using a Sanilabs neutral cleaner or maintainer. Burnish (1500-3000 rpm) **DuraGloss** Floor Finish as required using a light synthetic / natural hair blend pad.

*See Material Safety Data Sheet for proper handling and safety instructions.*